



AGRICULTURAL AIR ASSISTED SPRAYERS



Gratifying the thirst of your crops...



AGRICULTURAL AIR ASSISTED MOUNTED SPRAYER

MODEL: MINI HD-200-FX DRG

SPECIFICATIONS

- TANK CAPACITY : 200 LTR
- SUCTION CAPACITY : 58 LPM / MAX 40 BAR
- PUMP TYPE : DIAPHRAGM – MADE IN ITALY
- GEAR BOX : 2 SPEED
- FAN : SIZE -600 MM (MADE BY DRAGONE,ITALY)
FRONT INTAKE STAINLESS STEEL
- SPRAY TIPS : BLANK CORE / HOLLOW CONE ALBUZ ATR
CERAMIC NOZZLES
- NOZZLE HOLDER : BRAGLIA – M82/65 ADJUSTABLE NOZZLES.
- NO OF NOZZLES : 10
- FILTERS & ,MIXER : INCLUSIVE OF SUCTION FILTER 100LPM
AND TANK MIXER
- CHASSIS : HOT GALVANIZED
- SPECIAL FEATURES : DIRECT SHAFT DRIVE, PTO DRIVEN @ 540 RPM
SUITABLE TO ALL MINI TRACTORS.
- PIPES : HIGH PRESSURE HYDRAULIC PIPES
- ACCESSORIES : SS. NUT & BOLTS AND CLAMPS
- CONTROLLER : M-170-BRAGLIA-ITALY
- WEIGHT : 166KG
- DIMENSION : LWH (1240X920X1060)mm



SPECIFICATIONS OF FAN

Blade Angle	Air Speed m/s		Air Volume m ³ /hour	Absorbed Power kw
Fan Inclination				
20°		7.1	7900	2.9
35°		8.9	12300	4.4
45°		10.9	14700	5.5
20°		9.1	10200	5.1
35°		12.5	15300	7.2
45°		14.6	18500	9.3



AGRICULTURAL AIR ASSISTED TRAILED SPRAYER

MODEL: HD600V600 DRG FX



SPECIFICATIONS

- TANK CAPACITY : 600 LTR
- SUCTION CAPACITY : 58 LPM / MAX 40 BAR
- PUMP TYPE : DIAPHRAGM PUMP- MADE IN ITALY
- GEAR BOX : 2 SPEED
- FAN : SIZE - 600MM (MADE BY DRAGONE-ITALY)
FRONT INTAKE STAINLESS STEEL
- SPRAY TIPS : BLANK CORE / HOLLOW CONE ALBUZ ATR
CERAMIC NOZZLES
- NOZZLE HOLDER : BRAGLIA - M82/65 ADJUSTABLE NOZLES
- NO OF NOZZLES : 10
- FILTERS & ,MIXER : INCLUSIVE OF SUCTION FILTER 160 LPM
& TANK MIXERS
- CHASSIS : HOT GALVANIZED
- SPECIAL FEATURES : PTO DRIVEN @540 RPM, WIDE ANGLE SHAFT,
SUITABLE TO ALL TRACTORS ABOVE 20 HP
- PIPES : HIGH PRESSURE HYDRAULIC PIPES
- ACCESSORIES : SS.NUT, BOLTS AND CLAMPS
- CONTROLLER : M-170-BRAGLIA-ITALY
- WEIGHT : 315 kg
- DIMENSION : LWH : (2855x1140x1175)mm

SPECIFICATIONS OF FAN

Blade Angle		Air Speed m/s		Air Volume m ³ /hour	Absorbed Power kw
Fan Inclination					
20°		7.1	7900	2.9	
35°		8.9	12300	4.4	
45°		10.9	14700	5.5	
20°		9.1	10200	5.1	
35°		12.5	15300	7.2	
45°		14.6	18500	9.3	



AGRICULTURAL AIR ASSISTED TRAILED SPRAYER

MODEL: KX600V600 FX-DOUBLE FAN

SPECIFICATIONS

- TANK CAPACITY : 600 LTR
- SUCTION CAPACITY : 70 LPM / MAX 50 BAR
- PUMP TYPE : DIAPHRAGM PUMP- MADE IN ITALY
- GEAR BOX : 2 SPEED
- FAN : SIZE - 600MM (MADE BY DRAGONE-ITALY)
FRONT INTAKE STAINLESS STEEL
- SPRAY TIPS : BLANK CORE / HOLLOW CONE ALBUZ ATR
CERAMIC NOZZLES
- NOZZLE HOLDER : BRAGLIA - M82/65 ADJUSTABLE NOZZLES
- NO OF NOZZLES : 10
- FILTERS & ,MIXER : INCLUSIVE OF SUCTION FILTER 160 LPM
& TANK MIXERS
- CHASSIS : HOT GALVANIZED
- SPECIAL FEATURES : PTO DRIVEN @540 RPM, WIDE ANGLE SHAFT,
SUITABLE TO ALL TRACTORS ABOVE 24 HP
- PIPES : HIGH PRESSURE HYDRAULIC PIPES
- ACCESSORIES : SS.NUT, BOLTS AND CLAMPS
- CONTROLLER : M-170-BRAGLIA-ITALY
- WEIGHT : 393 kg
- DIMENSION : LWH : 2945x1140x1175)mm



SPECIFICATIONS OF FAN

Blade Angle			Air Speed m/s	Air Volume m ³ /hour	Absorbed Power kw
Fan Inclination					
20°			18.2	14300	5.6
35°			25.1	19200	10.3
45°			32.3	24300	14.2
20°			24.2	18300	10.0
35°			33.9	25700	16.2
45°			41.4	32100	19.9

AV AGRITECH INPUTS PVT LTD

PLOT NO - 2128 , PHASE II INDUSTRIAL ESTATE, RAI DIST. SONIPAT - 131029. HARYANA (INDIA)

Ph. 0124-4108631, 4108632 Mob.: +91-8983535711 CIN: U01122DL2007PTC163565

E-mail: avagri@gmail.com | Website: www.krishispray.com